

PIXMA ENDURANCE G7065 WHEN MORE INK MATTERS





Our refillable PIXMA ENDURANCE G7065 **comes with two additional black inks in the box.** The G7065 is a multifunction ink tank printer delivering high yield, quality and functionality at a low cost per page.

Think about your ink

How much printing are you doing at home or in the office? The Cloud Connected PIXMA ENDURANCE G7065 is a multi-tasker's dream printer. Delivering on the best of PIXMA's Multi-Function features such as Print, Copy, Scan and Fax– with ink tanks that hold Canon's pigment inks, it never fails to deliver quality, crisp text and stunning documents.

Bigger ink tanks, mean more pages

It's simple really, the G7065 can deliver up to 7,700 colour pages and up to 18,000 black and white pages (from three black ink bottles) on A4. How do you get so much ink? Every PIXMA ENDURANCE G7065 comes with 4 integrated ink tanks and 4 ink bottles – which you can simply fill and then start printing. You can also purchase refill bottles to top up when you run out – maintaining a low cost per print.

Ink isn't just an add on

Canon PIXMA prides itself on design, that's why we just haven't attached the ink tanks to the side of the printer, but seamlessly integrated it into the design. This will ensure that your new PIXMA ENDURANCE G7065 can fit into any home or home office environment.



PIXMA ENDURANCE G7065

WHEN MORE INK MATTERS



More Ink

- Refill your ink tanks with enhanced mess-free bottles. Boost uptime with a 350-sheet plain paper capacity and print up to 6,000 pages from a black bottle or 7,700 pages from a colour set, keeping the quality with a low cost-per-page.
- The ink bottles come with an easy one-step handling process that removes all fuss and mess with a special ink bottle nozzle that reduces spillage.



Connected

- Print documents and photos with the convenience of using a smart device, utilising PIXMA Cloud Link. PIXMA Cloud Link now includes Instagram and SlideShare in addition to existing cloud services such as Facebook, Dropbox and Google Drive.
- Connect to your smart device using the Canon Print Inkjet/ SELPHY app and print your documents off your smart phone.

Which inks can I use with my printer?



GI60PGBK Estimated Ink Yield A4 document: 6000



GI60C Estimated Ink Yield A4 document: 7700



2-Line mono LCD with tiltable front panel

Multifunctionality and a tiltable front panel with 2-Line LCD ensures compactness and practicality. Ideal for budding entrepreneurs at home or in a small office.



Reliability

- The giant ink tanks are seamlessly integrated into the printer, rather than attached to the side. This will ensure that your new PIXMA can fit into any home or home office environment.
- Rest assured with printer components of Canon quality and reliability, utilising the latest FINE technology.
- A simple auto on and off feature will save you energy by ensuring that your printer is not constantly switched on and using power.



GI60M Estimated Ink Yield A4 document: 7700



GI60Y Estimated Ink Yield A4 document: 7700



Technical Specifications

PIXMA ENDURANCE G7065

PIXMA G7065 Technical Specifications

| PIXMA G7065 Technical Specif | ications | |
|---------------------------------------|---|--|
| Printer Functions | | |
| Ink Type | Permanent (Refillable ink tanks) | |
| | | |
| Printing Resolution | 4800 (horizontal) x 1200 (vertical) dpi | |
| Document Print Speed ¹ | B&W: 13 ipm, Colour: 6.8 ipm | |
| Photo Print Speed ² | Approx. 45 seconds (4"x6" borderless) | |
| Deale Law Distance 3 | Top/Bottom/Right/Left margin: each 0 mm | |
| Borderless Printing ³ | (Supported Paper Size: A4/LTR/4"x6"/5"x7"/8"x10"/Square (5" x 5", 4«x4«, 89x89mm) | |
| | Top margin: 3 mm, Bottom margin: 5 mm, | |
| Bordered Printing | Left/Right margin: each 3.4 mm (LTR/LGL: Left: 6.4 mm, Right: 6.3 mm) | |
| Paper Capacity | | |
| Paper Capacity | Rear Tray: Max 10 sheets (photo paper) or 80 sheets (plain paper). Cassette: Max 250 sheets (plain paper) | |
| Commente d'Dan en Cince | A4, A5, B5, Letter. Legal, Envelopes (DL,COM10), 4"x6", 5"x7", 7"x10", 8"x10", Custom size (width 55mm – 215.9mm, | |
| Supported Paper Sizes | length 89mm – 676mm), Square (5"x5", 4"x4", 89x89mm) | |
| | Plain Paners 64 105 g/m ² . Concer aposicilly appear may paner unicht um to 200 g/m ² . (Photo Paner Bro Platinum | |
| Supported Paper Weights | Plain Paper: 64-105 g/m ² , Canon specialty paper: max paper weight : up to 300 g/m ² (Photo Paper Pro Platinum | |
| | PT-101) | |
| Auto Double Sided Printing | Yes – Plain Paper only | |
| Protocol | SNMP, HTTP, TCP/IP(IPv4/IPv6) | |
| Frequency Band / Channel ⁸ | 2.4GHz, 1-13 | |
| Wireless LAN Range | Range indoor 50m (depend on the transmission speed and conditions) | |
| Wireless LAN Security | | |
| Wireless LAN Network Type | | |
| Mobile Phone/Tablet Printing | Available | |
| - | | |
| Memory Card Printing | | |
| PC Interface | Available | |
| Copier Functions | | |
| Speed ⁶ | sFCOT/ Colour Simplex Approx. 22 sec | |
| Speed | sESAT / Colour Simplex Approx. 3.9ipm | |
| Multiple Copy | Max 99 pages (black/ colour) | |
| Scanner Functions | | |
| Scanner Type | Flatbed, ADF and CIS colour scanner | |
| Scanning resolution ⁴ | | |
| - | | |
| Scanning Bit Depth (Input/ | Grayscale; 16bit/8bit Colour: RGB each 16bit/8bit | |
| Output) | | |
| Scanning Speed ⁵ | A4 Colour/ 300 dpi – Approx. 3.5ms/line. A4 Greyscale: 300 dpi – Approx 1.5ms/line | |
| Fax Functions | | |
| Туре | Desktop Transceiver (Super G3/Color Communication) | |
| Transmission Speed | Black: 3 seconds, Colour: 1 minute | |
| Resolution | Colour: 200dpix200dpi | |
| | | |
| Transmission/ Reception | Approx. 50 pages | |
| Memory | | |
| Automatic Dialling | Group Dialing: max 19 locations | |
| PC FAX | Available for Mac and Windows, 1 location as a destination number only. B/W transmission only. | |
| Connectivity | | |
| Smartphone or tablet | Available | |
| | | |
| PIXMA cloud link from printer | | |
| Print from Email | | |
| Google Cloud Print | Available | |
| Apple Air Print | Available | |
| PIXMA Printing Solutions | Available | |
| Cloud Apps | Facebook, Dropbox, Google Drive, Instagram, SlideShare | |
| General Features ⁹ | | |
| Interface | High Speed USB | |
| Quiet Mode | | |
| | | |
| | Rear Tray and Cassette | |
| ADF | | |
| Power Source | | |
| Power Consumption | Standby (scanning lamp is off) USB connection to PC: approx. 1.0W, OFF. (All ports connected) Approx. 0.3W OFF. | |
| Power Consumption | Copying (USB connection to PC) approx. 15W | |
| Recommended Environment ⁷ | Temperature: 15-30°C Humidity: 10 - 80%RH (no dew condensation) | |
| Dimensions (W x D x H) | | |
| | Approx. 9.6kg | |
| weight | Approx. story | |
| | | |



Technical Specifications

PIXMA ENDURANCE G7065

Disclaimers:

*2: *3:

*4: *5: *6: *8: *10:

*11 *12 *14 *15 *16 *17 *18 *19 *20 *23 *24: *25: *26: *27: *28:

*29: *30

*31 *32 *33

| Ink droplets can be placed with a pitch of 1/4800 inch at minimum. | |
|---|--|
| Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. | |
| Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing | time on host computer. |
| Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc. | |
| Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers | |
| TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system. | |
| Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. | |
| The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included. | |
| Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. | |
| Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. | |
| Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming | up time. |
| Can be used by attaching the adapter that is separately sold in the market. | |
| Resolution may be changed between Direct print and printing from PC. | |
| It is NOT supported via Network. | |
| The amount of image extension beyond the paper cannot be adjusted. | |
| Plain paper is printed bordered automatically, regardless of the camera settings. | |
| Not supported for disk label print. | |
| Image data taken by DCF (Ver.1.0/2.0) -compliant digital cameras, camcorders or camera phones and recorded in JPEG (Exif-compliant) format. | |
| Function depends on the connected digital cameras, camcorders or camera phones. | |
| Support size depends on the layout. | |
| Only 'high' mode available as for the printer without LCD. | |
| Non-support for 2/4/9/16-up in sticker printing as well as date/file number printing in disc label printing. | |
| As for '4-up' print layout, either file number or date can be printed at one time. | |
| The performance of the printer may be reduced under certain temperature and humidity conditions. | |
| For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions. | |
| When printing ISO/JIS-SCID N2 on 4"x6" Photo Paper Plus Glossy II using default settings. | |
| Acoustic Noise is measured based on ISO7779 standard with default setting. | |
| Print: When printing ISO/JIS-SCID N2 on A4 size plain paper using default settings. | |
| Copy: When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. | |
| Specifications are subject to change without notice. | |
| 1-11 in US, CND, LTN, BRA, TW and HK. (Bingen does NOT have HK model. Hong-Kong will treat ASA model.) | |
| Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. | |
| Color document fax transmission speed is based on default setting using Canon Color Fax Test Sheet. | |
| Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc. | |
| Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1. | |
| Not supported for AirPrint. | |
| Tupical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly, switched among operational mode, sleep mo | de, and power-off mode for 5 days, and that it will be either in |

Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using. TEC measurement procedure regulated in International ENERGY STAR Program.

